

# SN-NVR2508E1-P8

# 8CH 1HDD NVR with 8CH POE



### Key features

- Up to 8ch IP cameras access
- Easy to use Same Interface of GUI/WEB/Client
- 1 SATA hard disk up to 8TB
- 1RJ45 10M/100M network interface
- 8ch POE Ports
- Simultaneous HDMI&VGA ,up to 4K output
- 2 x 2.0 USB Host
- 8ch Alarm Input, 1ch Alarm output
- 1ch Audio I/O

### Dimension

### Interface Introduction

### Specifications

VIDEO/AUDIO INPUT	
Video Input	8ch h.265/h.264
Incoming Bandwidth	60Mbps ,(main stream 48Mbps ,sub stream 12Mbps)
Outgoing Bandwidth	80Mbps
Audio Input	G711_A/G711_U
VIDEO/AUDIO OUTPUT	
Live View/Playback/Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/720P/D1/VGA/CIF/QCIF
Frame Rate	8MP/6MP/5MP/4MP/3MP/1080P@30fps;
Live View/Playback Capacity	Live View 8ch 720P/4ch 1080P/1ch 8MP @30fps Playback 8ch 720P/4ch 1080P/1ch 8MP
HDMI/VGA Output	HDMI : 3840x2160/60Hz,1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz VGA :1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz
Audio Output	1ch,Line out
HARD DISK	
SATA HDD	1 SATA interface for 1HDD
Mounting Mode	Embedded
Capacity	Up to 8TB for each disk
NETWORK	
Network Interface	1 RJ45 10M/100M
Protocol	RTP/RTCP,TCP/UDP,HTTP,DHCP,DNS,NTP
POE Interface	8ch 100Mbps,IEEE802.3af
POE Max Power	80W
INTERFACE	
HDMI/VGA	1ch HDMI, 1ch VGA
USB	USB 2.0 x2
Audio I/O	1ch MIC in,1ch audio line out
Alarm I/O	8ch Alarm input ,1ch Alarm output
Reset Button	N/A
GENERAL	
Power Supply	AC110-220V
Power Consumption	100W
Operating Temperature	-10°C ~ 45°C (14°F ~ 113°F )
Operating Humidity	0% - 90% RH
Chassis	1U
Product Dimensions	255 × 235 × 47.5mm
Product Weight	1kg